

TEHNIČKE KARAKTERISTIKE



RADNI USLOVI

pH vrednost: 7-8.3
Radni pritisak: 6 bar
Ispitni pritisak: 12 bar

Δt	EL 5/40	EL 5/50	EL 5/60	EL 7/40	EL 7/50	EL 7/60	EL 9/40	EL 9/50	EL 9/60
5	13	16	20	14	18	22	16	20	25
10	35	44	53	39	49	59	44	54	67
15	64	79	96	71	88	106	79	98	119
20	98	120	144	109	133	161	121	148	180
25	136	165	199	151	184	222	168	205	248
30	179	215	259	198	240	288	221	267	322
35	224	269	323	249	300	359	277	334	402
40	273	326	391	303	364	435	337	405	486
45	325	387	463	360	431	516	401	480	576
50	380	451	539	421	502	600	469	560	670
55	437	518	618	485	577	688	540	642	768
60	497	587	700	551	654	780	614	729	870
65	559	659	785	620	735	875	691	818	976
70	624	734	873	692	818	973	771	911	1085
75	691	811	964	766	904	1074	854	1007	1198
80	760	891	1058	843	993	1178	939	1105	1314
Km	1,1768	1,5621	1,9558	1,3037	1,739	2,1754	1,451	1,9391	2,4518
n	1,4766	1,4482	1,4362	1,4768	1,4484	1,4365	1,4771	1,4481	1,4341
Visina (mm)	675	675	675	945	945	945	1250	1250	1250
Širina (mm)	430	530	630	430	530	630	430	530	630
Osn.rast.priklj (mm)	400	500	600	400	500	600	400	500	600
Zapremina vode (l)	0,81	1,16	1,6	1,2	1,62	2,24	1,49	2,2	2,92
Masa (kg)	2,29	2,61	2,92	3,17	3,65	4,1	4,11	4,69	5,25